



Aoraki Specification Sheet



ALL DESIGNS ARE V-GROOVE AS STANDARD. SQUARE, CHAMFER OR U-GROOVE OPTIONS ARE AVAILABLE ON REQUEST.

6 x 3mm V-GROOVE DETAIL



Door Weights - kg/m²

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

Aoraki Grooving Dimensions (mm)

Side Stile Width and Number	Panel Height and Number
1980	110 x 1
2200	110 x 1
2400	110 x 1
2550	110 x 1
2700	110 x 1

Core Availability				Available Finishes		Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide			
	Hollow	Polystyrene	Solid	Un-Primed	U.V Primed		Rails	Stiles	Lockblocks
1980 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Hollow (1980)	Ex 35mm	Ex 35mm	400 x 70mm
Up to 2400 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Hollow (Up to 2400)	Ex 140mm	Ex 35mm	800 x 70mm
2700 High	•	•	•	MTO	MTO	Polystyrene	Ex 35mm	Ex 35mm	400/800 x 70mm
Oversize	N/A	•	N/A	MTO	N/A	Solid (Up to 2400)	Ex 140mm	Ex 35mm	N/A
						960mm Wide +	Ex 105mm	Ex 105mm	N/A
						>2400mm High	Ex 105mm	Ex 105mm	N/A

Skin and Thickness Options (MDF Skins)					
	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Oversize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options