


Parnell Specification Sheet



ALL DESIGNS ARE V-GROOVE AS STANDARD. SQUARE, CHAMFER OR U-GROOVE OPTIONS ARE AVAILABLE ON REQUEST.

6 x 3mm V-GROOVE DETAIL



Door Weights - kg/m²

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

Parnell Grooving Dimensions (mm)

Side Stile Width and Number		Mid Stile Width and Number
410	110 x 2	47.50 x 3
460	110 x 2	60.00 x 3
510	110 x 2	72.50 x 3
560	110 x 2	85.00 x 3
610	110 x 2	97.50 x 3
660	110 x 2	110.00 x 3
710	110 x 2	122.50 x 3
760	110 x 2	135.00 x 3
810	110 x 2	147.50 x 3
860	110 x 2	160.00 x 3
910	110 x 2	172.50 x 3
960	110 x 2	185.00 x 3
1010	110 x 2	197.50 x 3
1060	110 x 2	168.00 x 4
1110	110 x 2	178.00 x 4
1160	110 x 2	188.00 x 4
1210	110 x 2	198.00 x 4
Parnell Top Rail		145
Parnell Bottom Rail		145

Core Availability	Available Finishes		
	Hollow	Polystyrene	Solid
1980 High	•	•	•
Up to 2400 High	•	•	•
2700 High	•	•	•
Oversize	N/A	•	N/A

Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide			
	Rails	Stiles	Lockblocks
Hollow (1980)	Ex 35mm	Ex 35mm	400 x 70mm
Hollow (Up to 2400)	Ex 140mm	Ex 35mm	800 x 70mm
Polystyrene	Ex 35mm	Ex 35mm	400/800 x 70mm
Solid (Up to 2400)	Ex 140mm	Ex 35mm	N/A
960mm Wide +	Ex 105mm	Ex 105mm	N/A
>2400mm High	Ex 105mm	Ex 105mm	N/A

Skin and Thickness Options (MDF Skins)					
	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Oversize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options