

ARCH03 Specification Sheet



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, AND POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. PLEASE NOTE TONING WILL VARY FROM DOOR TO DOOR.

SHELTERED EXTERIOR OPTIONS AVAILABLE.

Door Weights - kg/m²

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0


Honeycomb Hollow Core



Particle Board Core



Polystyrene Core



ARCH03 Specialty Veneer Door Details

Description	Outer border is Tasmanian Oak, mid panel is Australian Jarrah
Stiles and Rails	145mm
Mid Panel Height	Door Height Less 290mm
Mid Panel Width	Door Width Less 290mm

Core Availability

	Hollow	Polystyrene	Solid
1980 High	•	•	•
2400 High	•	•	•
2700 High	•	•	•
Oversize	N/A	N/A	N/A

Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

	Rails	Stiles	Lockblocks
Hollow	Ex 35mm	Ex 35mm	400 x 70mm*
Polystyrene	Ex 35mm	Ex 35mm	400 x 70mm*
Solid	Ex 35mm	Ex 35mm	N/A
960mm Wide +	Ex 105mm	Ex 105mm	N/A
>2400mm High	Ex 105mm	Ex 105mm	N/A

Skin and Thickness Options

	36mm	39mm	42mm
Hollow	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	4.75mm Skin	4.75mm Skin	6.0mm Skin

- 'Oversize' is doors over 1210mm wide or 2700mm high
- Staining veneer doors is at your own risk. Hallmark Group accepts no responsibility for the finished quality of a stained veneer door
- All architectural collection doors are made to order

- * All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overheight doors