


MLN2 Specification Sheet



ALL DOORS AVAILABLE
UP TO 2700X1210MM.

Door Weights - kg/m²

Solid 28.5
Steel per L/M 2.0



AVAILABLE IN ANY
OF THE FOLLOWING
SPECIES
(other species may be
available on request)



Skin and Thickness Options

	39mm	40.5mm	42mm
Exterior	N/A	5.5mm Skin	N/A
Interior	6mm Skin	N/A	6mm Skin
Oversize	not available		

Door Frame Configuration Doors 410-910mm Wide

	Rails	Stiles
Solid Core	Ex 35mm	Ex 35mm
960mm Wide +	Ex 105mm	Ex 105mm
>2400mm High	Ex 105mm	Ex 105mm

MLN2 Specialty Veneer Door Details

Uses	Milano doors are suitable for sheltered exterior applications where solid timber would often warp, twist or crack
Description	Milano doors are engineered timber doors using exterior plywood substrate and bonded using marine grade glue
Features	the MLN2 door has vertical grain with vertical grooving as per the detail shown. All Milano doors have concealed clashing's to give a completely solid look
Species Shown	NZ Rimu
Groove Spacing	Refer to MLN2 grooving dimensions table

MLN2 Grooving Dimensions (mm)

	Side Stile Width and Number	Mid Stile Width and Number
410	110 x 2	95.00 x 2
460	110 x 2	80.00 x 3
510	110 x 2	96.66 x 3
560	110 x 2	85.00 x 4
610	110 x 2	97.50 x 4
660	110 x 2	88.00 x 5
710	110 x 2	98.00 x 5
760	110 x 2	90.00 x 6
810	110 x 2	98.33 x 6
860	110 x 2	91.43 x 7
910	110 x 2	98.57 x 7
960	110 x 2	92.50 x 8
1010	110 x 2	98.75 x 8
1060	110 x 2	93.33 x 9
1110	110 x 2	98.88 x 9
1160	110 x 2	94.00 x 10
1210	110 x 2	99.00 x 10

- 'Oversize' is doors over 1210mm wide or 2700mm high
- Interior options available
- All Milano doors are made to order
- Staining veneer doors is at your own risk. Hallmark Group accepts no responsibility for the finished quality of a stained veneer door