




Flush Panel Glazing Option 13



FLUSH




REBATED




Door Weights - kg/m²

| | |
|---------------|------|
| Hollow | 10.5 |
| Polystyrene | 10.5 |
| Solid | 28.5 |
| Steel per L/M | 2.0 |

4.75MM MDF SKIN
(FOR INTERIOR USE)



4.75MM TEMPERED
HARDBOARD SKIN
(FOR SHELTERED
EXTERIOR USE)



PLEASE NOTE: GLASS IS NOT INCLUDED. ALL PANELS ARE BEADED WITH REBATED BEADING AS STANDARD. FLUSH BEADING AVAILABLE ON REQUEST.

Vision Panel Option 13 Dimensions (mm)

| | |
|---------------------------|-------------------------|
| Top Rail | 110mm |
| Side Stile | 110mm |
| Solid Bottom Panel Height | 935mm |
| Glazing Opening Width | 200mm |
| Glazing Opening Height | Door Height Less 1045mm |

| | Core Availability | | | Available Finishes | |
|-----------------|-------------------|-------------|-------|--------------------|---------------------|
| | Hollow | Polystyrene | Solid | Un-Primed | U.V Primed |
| 1980 High | • | • | • | MTO | Ex-Stock (38mm S/C) |
| Up to 2400 High | • | • | • | MTO | Ex-Stock (38mm S/C) |
| 2700 High | • | • | • | MTO | MTO |
| Oversize | N/A | • | N/A | MTO | N/A |

| | Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide | | |
|---------------------|--|----------|----------------|
| | Rails | Stiles | Lockblocks |
| Hollow (1980) | Ex 35mm | Ex 35mm | 400 x 70mm |
| Hollow (Up to 2400) | Ex 35mm | Ex 35mm | 800 x 70mm |
| Polystyrene | Ex 35mm | Ex 35mm | 400/800 x 70mm |
| Solid (Up to 2400) | Ex 140mm | Ex 35mm | N/A |
| 960mm Wide + | Ex 105mm | Ex 105mm | N/A |
| >2400mm High | Ex 105mm | Ex 105mm | N/A |

Skin and Thickness Options (MDF Skins)

| | 34.5mm | 37mm | 38mm | 39.5mm | 42mm |
|-------------|-------------|------------|-------------|-------------|------------|
| Hollow | N/A | N/A | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Polystyrene | 4.75mm Skin | 6.0mm Skin | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Solid | N/A | N/A | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Oversize | N/A | 6.0mm Skin | N/A | N/A | 6.0mm Skin |

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options