

## MLN3 Specification Sheet






ALL DOORS AVAILABLE  
UP TO 2700x1210MM.

Door Weights - kg/m<sup>2</sup>

Solid 28.5

Steel per L/M 2.0



AVAILABLE IN ANY OF THE  
FOLLOWING SPECIES  
(other species may be  
available on request)



American  
White Oak



Rimu



Blackwood



Cedar



Jarrah



Tasmanian  
Oak

### MLN3 Specialty Veneer Door Details

Uses	Milano doors are suitable for sheltered exterior applications where solid timber would often warp, twist or crack
Description	Milano doors are engineered timber doors using exterior plywood substrate and bonded using marine grade glue
Features	The MLN3 door has vertical grain with horizontal and vertical grooving as per the detail shown. All Milano doors have concealed clashing's to give a completely solid look
Species Shown	Australian Blackwood
Stile Width	110.00
Rail Height	Door Height Divided by 6

### Skin and Thickness Options

	39mm	40.5mm	42mm
Exterior	N/A	5.5mm Skin	N/A
Interior	4.75mm Skin	N/A	6mm Skin
Oversize	not available		

### Door Frame Configuration Doors 410-910mm Wide

	Rails	Stiles
Solid Core	Ex 35mm	Ex 35mm
960mm Wide +	Ex 105mm	Ex 105mm
>2400mm High	Ex 105mm	Ex 105mm

- 'Oversize' is doors over 1210mm wide or 2700mm high
- Interior options available
- All Milano doors are made to order
- Staining veneer doors is at your own risk. Hallmark Group accepts no responsibility for the finished quality of a stained veneer door