

MDF Flush Panel Specification Sheet



Door Weights - kg/m²

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

Available Finishes

	Un-Primed	U.V Primed
1980 High	MTO	Ex-Stock
2400 High	MTO	Ex-Stock
2700 High	MTO	MTO
Oversize	MTO	N/A

Core Availability

	Hollow	Polystyrene	Solid
1980 High	(Ex-Stock)	MTO	(Ex-Stock)
2400 High	(Ex-Stock)	MTO	(Ex-Stock)
2700 High	MTO	MTO	MTO
Oversize	N/A	•	N/A

Skin and Thickness Options (MDF Skins)

	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Oversize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All Stock doors are hollow core
- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- 2400mm doors ex stock have 250mm particle board ends
- All hollow and polystyrene doors have double lock blocks
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options