

## ARCH07 Specification Sheet



ARCH07 DOORS ARE AVAILABLE IN SOLIDCORE ONLY. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. PLEASE NOTE TONING WILL VARY FROM DOOR TO DOOR.

SHELTERED EXTERIOR OPTIONS AVAILABLE.

### Door Weights - kg/m<sup>2</sup>

Solid	28.5
Steel per L/M	2.0

### Particle Board Core



### ARCH07 Specialty Veneer Door Details

<b>Description</b>	Stile is Australian Jarrah, main panel is Tasmanian Oak
<b>Veneer Position</b>	Australian Jarrah stile is 225mm wide, Tasmanian Oak makes up the balance of the door
<b>Top, Bottom and Mid Rails (Per Rail)</b>	Door Length Less 360mm Divided by 5
<b>Side Stiles</b>	110mm
<b>Glazing Opening Width</b>	Door Width Less 220mm
<b>Glazing Opening Height</b>	90mm

### Core Availability

	Hollow	Polystyrene	Solid
1980 High	N/A	N/A	•
2400 High	N/A	N/A	•
2700 High	N/A	N/A	•
Oversize	N/A	N/A	N/A

### Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

	Rails	Stiles	Lockblocks
Solid	Ex 35mm	Ex 35mm	N/A
960mm Wide +	Ex 105mm	Ex 105mm	N/A
>2400mm High	Ex 105mm	Ex 105mm	N/A

### Skin and Thickness Options

	36mm	39mm	42mm
Solid	4.75mm Skin	4.75mm Skin	6.0mm Skin

- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- All architectural collection doors are made to order
- Staining veneer doors is at your own risk. Hallmark Group accepts no responsibility for the finished quality of a stained veneer door