


## Flush Panel Glazing Option 5

## Hallmark Classic Collection



PLEASE NOTE: GLASS IS NOT INCLUDED. ALL PANELS ARE BEADED WITH REBATED BEADING AS STANDARD. FLUSH BEADING AVAILABLE ON REQUEST.



## Vision Panel Option 5 Dimensions (mm)Top, Bottom and Mid Rails (Per Rail)Door Height Less 600mm Divided by 4Side Stile110mmGlazing Opening Width200mmGlazing Opening Height200mm

	Core Availability			Available Finishes		Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide			
	Hollow	Polysty- rene	Solid	Un- Primed	U.V Primed		Rails	Stiles	Lockblocks
						Hollow (1980)	Ex 35mm	Ex 35mm	400 x 70mm
1980 High	•	•	•	мто	Ex-Stock (38mm S/C)	Hollow (Up to 2400)	Ex 35mm	Ex 35mm	800 x 70mm
Up to	oto • •	•	MEG	Ex-Stock	Polystyrene	Ex 35mm	Ex 35mm	400/800 x 70mm	
2400 High				MTO	(38mm S/C)	Solid (Up to 2400)	Ex 140mm	Ex 35mm	N/A
2700 High	•	•	•	МТО	MTO	960mm Wide +	Ex 105mm	Ex 105mm	N/A
Oversize	N/A	•	N/A	МТО	N/A	>2400mm High	Ex 105mm	Ex 105mm	N/A

Skin and Thickness Options (MDF Skins)											
	34.5mm	37mm	38mm	39.5mm	42mm						
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin						
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin						
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin						
Oversize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin						

• All doors over 1210 wide supplied un-primed

• 'Oversize' is doors over 1210mm wide or 2700mm high

All hollow and polystyrene doors have double lock blocks
Stock doors are standard sizes between 410mm

and 910mm wide

 Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options

0800 846 237 | sales@hallmarkgroup.co.nz