



CLASS 2

Building Product Information Sheet

Product name:

Hallmark Veneer

Product line:

Hallmark Veneered Panel Ranges

Product description and its intended use:

Hallmark Veneer produce decorative timber veneer panel from a wide range of species for the production of veneer panel and doors. The veneer itself is a timber layer 0.6mm thick which is pressed onto a substrate (usually MDF or Ply). Numerous cutting and matching options are available to affect unique aesthetic outcomes.

Product identifier:

Hallmark Veneered Panel is categorised into Native Range, Exotic Species Range, Eveneer (recon) Range, Luxe Range and Harmony Range:

NZ Native Range – NZ Tawa, Rimu Colour, Rimu Economy, Rimu Heart, Silver Beech, Totara – www.hallmarkgroup.co.nz/veneer-nz-native-range

Exotic Species Range – American Cherry, American Walnut, American White Ash, American White Oak, Anegre, Blackbutt, Eucalyptus Ash, Eucalyptus Oak, European Beech, European Birch, European Oak, Hoop Pine, Jarrah, Lusitanica, Maple, Oregon, Radiata Pine, Sapele, Smoked Oak, Spotted Gum, Tasmanian Blackwood, Tasmanian Blue Gum, Western Cedar – www.hallmarkgroup.co.nz/veneer-exotic-species-range

Eveneer Range – Angora, Chinchilla, Cumulus, Even Walnut, Havana, Metro, Ravenna, Romano, Umber, Xilo Two-Flamed White – www.hallmarkgroup.co.nz/veneer-eveneer-range

Luxe Range – American White Oak (x6 layup, cutting style & finishing options) – www.hallmarkgroup.co.nz/veneer-luxe

Harmony Range – American White Ash, American White Oak, Blackbutt, Eucalyptus Oak, Lusitanica, Rimu, Silver Beech, Tasmanian Blackwood (x layup variations) - www.hallmarkgroup.co.nz/veneer-harmony

Refer to www.hallmarkgroup.co.nz/veneerpanel for variant-specific information.

Place of manufacture:

New Zealand

Legal and trading name of the manufacturer(s):

Hallmark Group Limited

Address for service: 355 Flaxton Road, Rangiora, Canterbury 7400, NZ

Website: www.hallmarkgroup.co.nz

Email address: info@hallmarkgroup.co.nz

Phone Number: 0800 846 237

NZBN: 9429037332532

Relevant Building Code clauses:

B2 DURABILITY: performance clause B2.3.1 (c)

F2 HAZARDOUS BUILDING MATERIALS: performance clauses F2.3.1, and for doors with glazing also F2.3.2 and F2.3.3

Statement on how the building product is expected to contribute to compliance:

B2 DURABILITY - B2.3.1 (c):

Hallmark Veneer has a durability beyond 5 years when correctly installed and maintained, based on historic use in-market for more than 30 years.

F2 HAZARDOUS BUILDING MATERIALS: F2.3.1

Hallmark Veneer is manufactured using inert, nontoxic materials.

Limitations on the use of the building product:

- Hallmark Veneer is for interior use, and must not be exposed to high levels of direct sunlight or large fluctuations in humidity. Veneer is a natural product, like all timber products it may fade or discolour over time in areas exposed to high levels of light, heat and air.
- This range is not suitable for use damp areas or exterior applications, as a flooring product or as kitchen counter top or splashback.
- Veneer panel used in kitchen and bathroom situations needs to be properly edge banded and sealed to ensure there is no moisture egress into the product, proper ventilation in these areas is also important.
- If used in a high wear area, suitable finishing systems must be used as advised by an experienced coatings professional.
- Veneer being a natural product, there will always be a level of feature that is specific to each specie; this could be pin knots, gum vein, small indentations, slanted and curved direction of grain in Quarter Cuts, off centre crown in crown cuts and paling fence effect in some ¼ cuts especially when stains are used as part of the finishing process. These are not defects but intrinsic features of natural wood veneer and its processing.

Design requirements that would support the use of the building product:

Hallmark Veneer Range is designed for, but is not limited to, use in projects within the following scope:

- Housing and residential apartment buildings, and their associated ancillary and outbuildings - interior use only.
- Commercial buildings, and their associated ancillary and outbuildings - interior use only.

Hallmark Veneer Range may be used in projects outside this scope if other parties such as architects or specifiers establish appropriate design and installation requirements.

Installation requirements:

- Installation requirements vary depending on intended use.
- Doors and panel must be stored flat in a clean, dry area away from direct sunlight. A flat MDF cover sheet must be placed on the surface at all times should it be exposed.

- Inspect product upon arrival for freight damage and visible defects. Hallmark must be notified within four days if damage has occurred. Any claims outside of this time frame cannot be recognised.
- Hallmark Veneer Panel and Doors must be installed in dry buildings only. Installation in situations with excessive air movement (i.e. buildings not at 'lock up' stage) void the warranty.
- It is essential that the right coating system is used, for example, two pack acrylic-urethane products with approved UV inhibitors for sealer and top coats.

Maintenance requirements:

- Veneer that becomes scratched or damaged should have the coating repaired immediately. Any repair work must be carried out under the instructions of the coating manufacturer.

Is the building product/building product line subject to warning or ban under section 26?:

No

Date: 01 / 10 / 23