


Flush Panel Glazing Option 8




PLEASE NOTE: GLASS IS NOT INCLUDED.
ALL PANELS ARE BEADED WITH REBATED
BEADING AS STANDARD. FLUSH
BEADING AVAILABLE ON REQUEST.

FLUSH



REBATED



Vision Panel Option 8 Dimensions (mm)

Top, Bottom and Mid Rails (Per Rail)	Door Length Less 600mm Divided by 5
Side Stiles	110mm*
Glazing Opening Width	Door Width Less 220mm**
Glazing Opening Height	150mm

* Side Stiles increase to 160mm when doors are ordered with steel stiffeners

** Glazing Opening Width formula with steel stiffeners changes to 'Door Width less 320mm'

	Core Availability			Available Finishes	
	Hollow	Polystyrene	Solid	Un-Primed	U.V Primed
1980 High	N/A	N/A	•	MTO	Ex-Stock (38mm S/C)
Up to 2400 High	N/A	N/A	•	MTO	Ex-Stock (38mm S/C)
2700 High	N/A	N/A	•	MTO	MTO
Oversize	N/A	N/A	N/A	MTO	N/A

	Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide		
	Rails	Stiles	Lockblocks
Hollow (1980)	N/A		
Hollow (Up to 2400)	N/A		
Polystyrene	N/A		
Solid (Up to 2400)	Ex 140mm	Ex 35mm	N/A
960mm Wide +	Ex 105mm	Ex 105mm	N/A
>2400mm High	Ex 105mm	Ex 105mm	N/A

	Skin and Thickness Options (MDF Skins)				
	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	N/A	N/A	N/A
Polystyrene	N/A	N/A	N/A	N/A	N/A
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Oversize	N/A	N/A	N/A	N/A	N/A

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high

- Stock doors are standard sizes between 410mm and 910mm wide

- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options