


## Tasman Specification Sheet



ALL DESIGNS ARE V-GROOVE AS STANDARD. SQUARE, CHAMFER OR U-GROOVE OPTIONS ARE AVAILABLE ON REQUEST.

6 x 3mm V-GROOVE DETAIL



**Door Weights - kg/m<sup>2</sup>**

|               |      |
|---------------|------|
| Hollow        | 10.5 |
| Polystyrene   | 10.5 |
| Solid         | 28.5 |
| Steel per L/M | 2.0  |

### Tasman Grooving Dimensions (mm)

| Side Stile Width and Number |         | Panel Height and Number |
|-----------------------------|---------|-------------------------|
| 1980                        | 110 x 2 | 513.33 x 3              |
| 2200                        | 110 x 2 | 586.66 x 3              |
| 2400                        | 110 x 2 | 653.33 x 3              |
| 2550                        | 110 x 2 | 703.33 x 3              |
| 2700                        | 110 x 2 | 753.33 x 3              |
| Tasman Top Rail             |         | 110                     |
| Tasman Mid Rails            |         | 110                     |
| Tasman Bottom Rail          |         | 110                     |

|                 | Core Availability |             |       | Available Finishes |                           |
|-----------------|-------------------|-------------|-------|--------------------|---------------------------|
|                 | Hollow            | Polystyrene | Solid | Un-Primed          | U.V Primed                |
| 1980 High       | •                 | •           | •     | MTO                | Ex-Stock (38mm H/C & S/C) |
| Up to 2400 High | •                 | •           | •     | MTO                | Ex-Stock (38mm H/C & S/C) |
| 2700 High       | •                 | •           | •     | MTO                | MTO                       |
| Oversize        | N/A               | •           | N/A   | MTO                | N/A                       |

| Stile, Rail and Lockblock Configuration<br>1980 up to 2400 High Doors 410-910mm Wide |          |          |                |
|--|----------|----------|----------------|
|  | Rails    | Stiles   | Lockblocks     |
| Hollow (1980)  | Ex 35mm  | Ex 35mm  | 400 x 70mm     |
| Hollow (Up to 2400)  | Ex 140mm | Ex 35mm  | 800 x 70mm     |
| Polystyrene  | Ex 35mm  | Ex 35mm  | 400/800 x 70mm |
| Solid (Up to 2400)   | Ex 140mm | Ex 35mm  | N/A            |
| 960mm Wide +   | Ex 105mm | Ex 105mm | N/A            |
| >2400mm High   | Ex 105mm | Ex 105mm | N/A            |

### Skin and Thickness Options (MDF Skins)

|             | 34.5mm      | 37mm       | 38mm        | 39.5mm      | 42mm       |
|-------------|-------------|------------|-------------|-------------|------------|
| Hollow      | N/A         | N/A        | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Polystyrene | 4.75mm Skin | 6.0mm Skin | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Solid       | N/A         | N/A        | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Oversize    | N/A         | 6.0mm Skin | N/A         | N/A         | 6.0mm Skin |

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options